

ONTEC S C1 60 NM ST W TM-OS.C1STN660W



No: 10A23



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797
Valid until:
24.06.2025



No:
B_BK_60212_0268
Valid until:
18.07.2026





No: 10A23



No: 10A23



Producer	TM Technologie
Category	emergency luminaires
Application	escape route lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Colour structure	smooth, gloss
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	282 lm
Light source	LED
Maximum light power	2.5 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	10 °C
Maximum temperature	40 °C
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm



2,5	8	18	-	-
3	8,5	20,5	-	-
4	9,5	25	-	-
5	9	27,5	-	-
6	6,5	28	-	-
7	5	26	-	-
8	4,5	23	-	-
9	4	20	-	-
10	4	15	-	-

* Some of mounting methods are possible only with additional accessory dedicated for that product.