

TM TECHNOLOGIE Sp. z o.o., Morawica 355, 32-084 Morawica, gm. Liszki, Poland, tel.: +48 12 444 60 60, fax: +48 12 350 57 34, www.tmtechnologie.pl

TM TECHNOLOGIE
emergency & evacuation lighting

TM.ONTEC S

IP 44 IP 65 LED	1h/3h	850 °C	□	人	♻️	210 ÷ 250 V AC 50 / 60 Hz 186 ÷ 254 V DC
-10 ÷ +40°C	COLD	-15 ÷ +40°C	CB, CBM, CBA	-15 ÷ +55°C	CBA	-10 ÷ +40°C
0.7 m	EAC	CNBP-FIB	CE			

A1

A2

B1

B2

A3

B3

1 CBA/CBM/D2/D2R/DA/D3/D3R/DL

TM-PROG

CBx≤10mm / Dx≤10mm

1.1

TM-PROG

CBx≤25mm / Dx≤40mm

! ±1 [mm]

! *B1, B2, B3 *A2, B2

Dimensions shown:

- Top View: 272^{*1}, 269, 252, 68, 35, 23, 296^{*B}, 127, 144, 25, 38, 2xø19
- Side View: 15, 75, ø19
- Front View: 15, 24, 40, 15, 40, 48^{*B}, 126^{*1}, 174^{*1}



